

EL MIRADOR, TAOS IMPROVEMENTS 2007 THROUGH PRESENT

[illegible]

- RADIANT FLOOR HEATING
- Stone Counters THROUGHOUT
- PORCELAIN TILE FLOOR THROUGHOUT



- No covered Patios
- Covered door PORTAL: 48 SQ. FT.

APPLICATION DATA SHEET

1.0 DESIGN DATA (Given - House)

- | | | |
|-----------------------------|---|---|
| 1.1 Building Location | = | EL Mirador Lot 24 |
| 1.2 Floor Area | = | 2594 + GARAGE 779 SQ. FT. |
| 1.3 Flat Ceiling Area | = | 2594 |
| 1.4 Net Wall Area | = | 2630 |
| 1.5 Window Area | = | 433 |
| 1.6 Door Area | = | 192 SQ. FT. |
| 1.7 Concrete Slab Perimeter | = | 263' |
| 1.8 Roof Insulation Used | = | → R-38 MIN FIBERGLASS
<small>- Roof Structure
- Broye Roof Ceiling</small> |
| 1.9 Window Type Used | = | Pella Triple Pane R-4 |
| 1.10 Doors Used (thickness) | = | WOOD 1 3/4" |
| 1.11 Wall Assembly | = | 2X8 FRAME W/ FIBERGLASS R-24
PLUS 2" EXT. INSUL. R-15 |

OFFICE USE ONLY

- | | | |
|----------------------------|---|----------------|
| 1.12 Perimeter Slab Insul. | = | 6.0 R Provided |
|----------------------------|---|----------------|

2.0 Table A-1 Data (Min. R Values Allowed by Code)

- | | | |
|-----------------------------------|---|-------|
| 2.1 Heating Degree Days | = | _____ |
| 2.2 Roof/Clg. R. | = | _____ |
| 2.3 Walls R | = | _____ |
| 2.4 Floor Slab Perimeter Insul. R | = | _____ |
| 2.5 Perimeter Insulation Depth | = | _____ |